

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/073522 A1

(51) International Patent Classification⁷: **F01L 7/02**
(21) International Application Number:
PCT/AU2005/000092

(22) International Filing Date: 28 January 2005 (28.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004900377 28 January 2004 (28.01.2004) AU

(71) Applicant (for all designated States except US): **BISHOP INNOVATION LIMITED** [AU/AU]; 10 Waterloo Road, North Ryde, NSW 2113 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **THOMAS, Andrew, Donald** [AU/AU]; 28 Hanovar Avenue, North Epping, 2121 (AU).

(74) Agent: **PAPPAS, Frank**; Bishop Innovation Limited, P.O. Box 135, North Ryde, NSW 1670 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PORT ARRANGMENT FOR A ROTARY VALVE ENGINE**



(57) Abstract: A axial flow rotary valve rotatable within a bore in a cylinder head (9) of an internal combustion engine has a port extending from a peripheral opening (4) to an axial opening at one end of the valve. The peripheral opening (4), which periodically communicates with a combustion chamber (30) through a window (8) in the bore, has a first trailing edge (13). The window (8) has a second trailing edge (12). The port closes from the combustion chamber (30) as the first trailing edge (13) passes the second trailing edge (12). The edges (12, 13) are disposed such that the instantaneous intersection point (17) of the two edges (12, 13) progressively moves away from the axial opening over at least 50% of the length of the window (8) as the port closes.



WO 2005/073522 A1